

Mid-level spreader systems



**System FSB 6 Mk II
75/2 AL MS
0473AM**

**System FSB 6 Mk II
75/2 CF MS
0473CM**

**System FSB 8 Mk II
75/2 AL MS
0773AM**

**System FSB 8 Mk II
75/2 CF MS
0773CM**

Bowl	75 mm	75 mm	75 mm	75 mm
Payload range	0 - 8 kg / 0-17.6 lb	0 - 8 kg / 0-17.6 lb	0 - 12 kg / 0-26.5 lb	0 - 12 kg / 0-26.5 lb
Counterbalance steps	15+0	15+0	15+0	15+0
Drag setting	3+0	3+0	7+0	7+0
Camera fitting	Sideload S	Sideload S	Sideload S	Sideload S
System weight	5.2 kg / 11.5 lb	4.7 kg / 10.4 lb	5.4 kg / 11.9 lb	4.9 kg / 10.8 lb
Height range	81 - 171 cm / 31.9 - 67.3 in	81 - 171 cm / 31.9 - 67.3 in	81 - 171 cm / 31.9 - 67.3 in	81 - 171 cm / 31.9 - 67.3 in
Transport length	87 cm / 34.3 in	87 cm / 34.3 in	87 cm / 34.3 in	87 cm / 34.3 in

Ground spreader systems



**System FSB 6 Mk II
75/2 AL GS
0471AM**

**System FSB 6 Mk II
75/2 CF GS
0471CM**

**System FSB 8 Mk II
75/2 AL GS
0771AM**

**System FSB 8 Mk II
75/2 CF GS
0771CM**

Bowl	75 mm	75 mm	75 mm	75 mm
Payload range	0 - 8 kg / 0-17.6 lb	0 - 8 kg / 0-17.6 lb	0 - 12 kg / 0-26.5 lb	0 - 12 kg / 0-26.5 lb
Counterbalance steps	15+0	15+0	15+0	15+0
Drag setting	3+0	3+0	7+0	7+0
Camera fitting	Sideload S	Sideload S	Sideload S	Sideload S
System weight	5.4 kg / 11.9 lb	4.9 kg / 10.8 lb	5.6 kg / 12.3 lb	5.0 kg / 11 lb
Height range	59 - 175 cm / 23.2 - 68.9 in	59 - 175 cm / 23.2 - 68.9 in	59 - 175 cm / 23.2 - 68.9 in	59 - 175 cm / 23.2 - 68.9 in
Transport length	87 cm / 34.3 in	87 cm / 34.3 in	87 cm / 34.3 in	87 cm / 34.3 in

Built for endurance.

Engineered to the highest standards with tough materials and precision components, FSB is built for endurance. With no variation in performance in the widest range of temperatures and environments, FSB is the first choice for outdoor operators.

