

### Description

#### NP-9X

NP-9X is the successor of the NP-L7S, the industry standard NP-style battery for powering audio equipment. It now features 96Wh, two D-Tap outputs, and a 5 LED power indicator. One of the D-Tap port is a D-Tap Advanced, which can also be a charge port when used with the IDX VL-DT1 charger. NP-9X is still compatible with all current accessories and chargers like the JL-2PLUS.



### Features



- 96Wh (14.4V / 6.6Ah) capacity
- Meets ≤ 100Wh passenger aircraft carry-on requirement
- 2x D-Tap outputs
- Charging via D-Tap (*compatible only with IDX VL-DT1 D-Tap charger*)
- 5 LED power indicator (*two-step LED allows for displaying 10% increments*)
- Compatible with all current accessories and chargers



### Specifications



<b>Capacity:</b>	96Wh (14.4V / 6.6Ah)
<b>Max Output Voltage:</b>	16.8V
<b>Nominal Voltage:</b>	14.4V
<b>Max Draw:</b>	4.6A / 50W ( <i>total of main connector and D-Taps</i> )
<b>End Voltage:</b>	11V
<b>Power Outputs:</b>	(1) D-Tap, (1) D-Tap Advanced
* D-Tap:	50W each
* D-Tap Advanced:	Compatible only with IDX VL-DT1 charger
<b>Additional Feature:</b>	5 LED Power Indicator
<b>Battery Protection:</b>	Over-charge/discharge/current, Thermal
<b>Ambient Temperature:</b>	To charge: 0°C~40°C
	To discharge: -20°C~45°C
	To store: -20°C~40°C
<b>Dimensions:</b>	184.5mm(W) x 71.2mm(H) x 24.7mm(D)
<b>Weight:</b>	520g approx.

IDX reserves the right to change the specifications contained herein without notice.