

# Specifications

	VENICE 2 with 8.6K image sensor (MPC-3628)	VENICE 2 with 6K image sensor (MPC-3626)
<b>General</b>		
Power Requirements	DC12 V (11.0 to 17.0 V) DC24 V (22.0 to 32.0 V)	
Power Consumption (Condition: 12 V DC Input, Temp 25 °C, without accessories)	Approx. 76 W (When recording X-OCN XT, 8.6K 3:2, 24FPS)	Approx. 73 W (When recording X-OCN XT, 6K 3:2, 24FPS)
Operating Temperature	0 to 40 °C	
Storage Temperature	-20 °C to 60 °C	
Mass (without lens, handle, VF attachment and accessories)	Approx.: 4.3 kg (9 lb 7.7 oz)	Approx.: 4.2 kg (9 lb 4.2 oz)
Dimensions	152 x 158 x 250 mm (WxHxD, excluding protrusions)	
<b>Camera</b>		
Imaging Device	35 mm full size, single-chip CMOS imager sensor	
Imaging Device Pixel Count	50.0M (Total)	24.8M (Total)
Built-In ND Filters	Clear, 0.3 (1/2), 0.6 (1/4), 0.9 (1/8), 1.2 (1/16), 1.5 (1/32), 1.8 (1/64), 2.1 (1/128), 2.4 (1/256)	
ISO Sensitivity	ISO800, ISO3200 (Dual Base ISO)	
Lens Mount	PL Mount E-mount (lever lock type, without supplied PL lens mount adaptor)	
Latitude	16 Stop	15+ Stop
Select FPS	5.8K 17:9 1-90FPS, 5.4K 16:9 1-90FPS 5.8K 6:5 1-48FPS** 8.2K 17:9 1-60FPS***, 7.6K 16:9 1-60FPS*** 8.6K 3:2 1-30FPS***	4K 2.39:1 1-12-FPS, 4K 17:9/3.8K 16:9 1-110FPS 4K 4:3 1-75FPS**, 4K 6:5 1-72FPS** 6K 2.39:1 1-90FPS***, 6K 17:9/6K 1.85:1/ 5.7K 16:9 1-72FPS*** 6K 3:2 1-60FPS***
<b>Recording</b>		
Recording Format (X-OCN)	X-OCN XT/ST/LT: 8.6K 3:2 (8640 x 5760): 23.98p, 24p, 25p, 29.97p 8.2K 17:9 (8192 x 4320): 23.98p, 24p, 25p, 29.97p, 47.95p*, 50p*, 59.94p* 7.6K 16:9 (7680 x 4320): 23.98p, 24p, 25p, 29.97p, 50p*, 59.94p* 5.8K 6:5 (5792 x 4854): 23.98p, 24p, 25p, 29.97p, 47.95p 5.8K 17:9 (5792 x 3056): 23.98p, 24p, 25p, 29.97p, 47.95p, 50p, 59.94p 5.4K 16:9 (5452 x 3056): 23.98p, 24p, 25p, 29.97p, 50p, 59.94p	X-OCN XT/ST/LT: 6K 3:2 (6048 x 4032): 23.98p, 24p, 25p, 29.97p, 47.95p, 50p, 59.94p 6K 2.39:1 (6048 x 2534): 23.98p, 24p, 25p, 29.97p, 47.95p, 50p, 59.94p 6K 1.85:1 (6054 x 3272): 23.98p, 24p, 25p, 29.97p, 47.95p, 50p, 59.94p 6K 17:9 (6054 x 3192): 23.98p, 24p, 25p, 29.97p, 47.95p, 50p, 59.94p 5.7K 16:9 (5674 x 3192): 23.98p, 24p, 25p, 29.97p, 50p, 59.94p 4K 6:5 (4096 x 3432): 23.98p, 24p, 25p, 29.97p, 47.95p, 50p, 59.94p 4K 4:3 (4096 x 3024): 23.98p, 24p, 25p, 29.97p, 47.95p, 50p, 59.94p 4K 17:9 (4096 x 2160): 23.98p, 24p, 25p, 29.97p, 47.95p, 50p, 59.94p 4K 2.39:1 (4096 x 1716): 23.98p, 24p, 25p, 29.97p, 47.95p, 50p, 59.94p 3.8K 16:9 (3840 x 2160): 23.98p, 24p, 25p, 29.97p, 50p, 59.94p

	VENICE 2 with 8.6K image sensor (MPC-3628)	VENICE 2 with 6K image sensor (MPC-3626)
Recording Format (ProRes)	ProRes 4444/ProRes 422 HQ 4K (4096x2160): 23.98p, 24p, 25p, 29.97p, 50p, 59.94p QFHD (3160x2160): 23.98p, 24p, 25p, 29.97p, 50p, 59.94p	
Recording Format (Audio)	LPCM 4ch, 24-bit 48-kHz	
<b>Inputs/Outputs</b>		
DC Input	XLR-type 4 pin (male)	
Battery DC Input	Square-shaped 5 pin connector	
DC Output	12 V: Lemo 2 pin x1 24 V: Fischer 3 pin x2	
SDI Output	BNC x4, (12G, 6G, 3G, 1.5G-SDI)	
HD MONI Output	BNC x1 (3G, 1.5G-SDI)	
HDMI Output	Type A x1	
VF	LEMO 26 pin	
Audio Input	XLR-type 5 pin (female) x1 (LINE/AES/EBU/MIC/MIC+48 V selectable) Internal mic x1	
Timecode Input	BNC x1	
Genlock Input	BNC x1	
AUX	BNC x1 (Timecode Output)	
Remote	8 pin x1	
Lens	12 pin x1	
Lens Mount Hot Shoe	4 pin x2, supporting Cooke /i Intelligent Electronic Lens System and ZEISS eXtended Data	
Network	RJ-45 type x1, 10BASE-T, 100BASE-TX	
External device connector	USB host, type-A x1	
Headphone Output	Stereo mini jack x1	
Speaker Output	Monoral	
Media type	AXS Memory A-Series slot x2 SD card slot x1	

\* X-OCN XT is not supported

\*\* CBKZ-3620A/AM/AW is required

\*\*\* CBKZ-3620F/FM/FW is required

©2021 Sony Corporation. All rights reserved.

Reproduction in whole or in part without written permission is prohibited.

Features, design, and specifications are subject to change without notice.

The values for mass and dimension are approximate.

\*SONY\* is a registered trademark of Sony Corporation.

All other trademarks are the property of their respective owners.

Please visit VENICE 2 website or contact your Sony representative for more information.

