



FSB 10 *Mk II*



Fluid, Smooth, Balanced

Capture the moment precisely

Redesigned with features from the revolutionary Sachtler aktiv fluid head range, FSB delivers precision movement with finely calibrated levels of drag and counterbalance for the perfect shot. The streamlined profile is built to withstand the toughest conditions to deliver repeatable, reliable camera support shot after shot.

- **Smooth operation.**
Create precision pans with smooth starts and soft stops.
- **Finely balanced.**
Delivering smooth pan-tilt fluid actions to match any camera payload from 0kg.
- **Always on the level.**
Innovative illuminated PrismBubble visible from any height – day or night.
- **Built for endurance**
Engineered to the highest standards with tough materials and precision components.



FSB 10 *Mk II* S2073-0001

Bowl size: 100mm with integrated flat base
Payload Range: 0 - 12 kg / 0 - 26.5 lb
Counterbalance steps: 15+0
Drag setting: 7+0
Camera fitting: Sideload S
Weight: 2.7 kg / 5.9 lb

Level: Illuminated PrismBubble
Sliding range: 120 mm / 4.7 in
Tilt range: +90° to -70°
Temperature range:
-40°C to +60°C / -40°F to +140°F

10



Fluid, Smooth, Balanced

1 Smooth operation.

Create precision pans with smooth starts and soft stops. The drag system delivers consistently smooth camera movements, fine-tuned to your payload.

2 Finely balanced.

Steady shots are standard with FSB. Delivering smooth pan-tilt fluid actions to match any camera payload from 0kg, the widest range of cameras can be finely balanced in the perfect position.

3 Always on the level.

Instant confirmation that the camera is level comes from the innovative illuminated PrismBubble visible from any height – day or night.

4 Built for endurance.

Engineered to the highest standards with tough materials and precision components, FSB is built for endurance. With no variation in performance in the widest range of temperatures and environments, FSB is the first choice for outdoor operators.



FSB Mk II



**System FSB 10 Mk II
ENG AL GS
1041M**



**System FSB 10 Mk II
ENG CF GS
1042M**



**System FSB 10 Mk II
ENG CF MS
1043M**

Spreader type	Ground spreader	Ground spreader	Mid-level spreader	
Bowl	100 mm	100 mm	100 mm	
Payload range	0 - 12 kg / 0 - 26.5 lb	0 - 12 kg / 0 - 26.5 lb	0 - 12 kg / 0 - 26.5 lb	
Counterbalance steps	15+0	15+0	15+0	
Drag setting	7+0	7+0	7+0	
Balance range	120 mm / 4.7 in	120 mm / 4.7 in	120 mm / 4.7 in	
Tilt range	+90° to -70°	+90° to -70°	+90° to -70°	
Camera fitting	Sideload S	Sideload S	Sideload S	
System weight	6.7 kg / 14.8 lb	6.2 kg / 13.7 lb	6.7 kg / 14.8 lb	
Height range with spreader	62 - 170 cm / 24.4 - 66.9 in	62 - 170 cm / 24.4 - 66.9 in	66 - 168 cm / 26 - 66.1 in	
Transport length	89 cm / 35 in	89 cm / 35 in	89 cm / 35 in	
Tripod stages	2	2	2	
Tripod material	Aluminium	Carbon fibre	Carbon fibre	