

### Dimmable, Low Profile and Light Weight



The Crossfade X, a low-profile linear light source, offers a simple, broad spectrum, tunable white light from a beautifully warm 2000K to a crisp 6000K.

Whether for lighting actors or environments, the time-tested power of its simplicity delivers vast versatility at an exceptional value. Use one as a key light, rig three for a 3-point lighting setup, install 10 as architectural lighting accents, or go big: stack 100 into a massive LED array with unprecedented energy efficiency for illuminating stage backings or for rigging above diffusion for the perfect skylight.

Intelligent mounting and AC cabling accessories add to its versatility. For example, the Crossfade X can retrofit legacy Kino packages to increase their output, color quality, and make dimmer compatible LED units.

#### **Tunable White Light**

The Crossfade X blends a warm 2000K diode and a cool 6000K diode generating a balanced, flicker-free color spectrum at any color mix.





#### **Simple Operation**

The new power switch allows for quick on/off operation with an easy-to-operate color control dial providing quick and simple tweaking in any environment.

# Scalable

Stack them in columns and rows to create large LED panels and arrays of any size, or line them up end-to-end for long linear lighting sources. Construct geometric patterns and 3D structures—endless visual possibilities abound!

### Self-Ballasted

For an easily-cabled light with a clean appearance, a single ended power input design receives industrystandard TRUE1 connector power cables without need for external AC-to-DC power adaptors. This design, coupled with TRUE1 Multibank Adaptors, saves time and energy on set by eliminating messy wiring looms.



# Accessories

**Mounting** – The injection molded Q-Block allows custom fabrication of your own mounting system or clean installation in architectural settings.

**Power** – TRUE1 Multibank Power Adaptors provide multiple outputs to simplify power cabling of 2x-6x unit arrays.

Crossfade X - 2ft



Color System	Tunable White	Tunable White	Tunable White
Lumens	2250	4500	9000
CT Range	2,000K - 6,000K	2,000K - 6,000K	2,000K - 6,000K
Veight	1.0lbs (0.45 kg)	1.9lbs (0.86 kg)	3.5lbs (1.59 kg)
imensions	24.5 x 1.5 x 1.5 in (622 x 38 x 38 mm)	48.75 x 1.5 x 1.5 in (1238 x 38 x 38 mm)	95 x 1.6 x 1.6 in (2413 x 41 x 41 mm)
attage	Max. 25W	Max. 50W	Max. 100W
ower	AC Input Power 120 VAC, 60 Hz at 0.3 A	AC Input Power 120 VAC, 60 Hz at 0.3 A	AC Input Power 120 VAC, 60 Hz at 0.3 A
Expected .amp Life	25.000 Hours	25.000 Hours	25.000 Hours

Crossfade X - Aft Crossfade X - Aft

