

[PARAMETER]

Focal Length	28 mm	32 mm	40 mm	55 mm	65 mm	75 mm	100 mm	135 mm	180 mm
Colour	Space Grey + Black								
Flare Option	Neutral / Blue								
Mount	PL / EF								
Aperture	T2.1-T22			T2.8-T22		T2.1-T22	T2.4-T22	T2.5-T22	T2.8-T22
Image Circle	φ31.5mm (S35)								
Construction of Optics	15 Elements in 13 Groups	15 Elements in 13 Groups	15 Elements in 14 Groups	14 Elements in 13 Groups	17 Elements in 12 Groups	15 Elements in 14 Groups	14 Elements in 13 Groups	16 Elements in 11 Groups	16 Elements in 11 Groups
Flange Distance	52mm (PL) / 44mm (EF)								
Close Focus (from sensor plane)	0.4m/1ft4in	0.4m/1ft4in	0.45m/1ft6in	0.6m/2ft	0.366m/1ft2.4in	0.84m/2ft9in	0.95m/3ft1in	0.99m/3ft3in	1.04m/3ft5in
Squeeze Factor	2x								
Iris Control	Manual (79°)	Manual (59°)	Manual (58°)	Manual (63°)	Manual (73°)	Manual (67°)	Manual(69°)	Manual(79°)	Manual(79°)
Focus Control	Manual (270°)				Manual (300°)				
Front Dia.	φ95mm/3.74"								
Length (from lens front to flange plane)	106.3mm/4.19"	105.7mm/4.16"	107.6mm/4.24"	108.4mm/4.26"	160mm/6.3"	126.9mm/4.99"	143.1mm/5.63"	160mm/6.3"	160mm/6.3"
Iris Blade	14	16							
Filter Size	M86								
Gear Pitch	0.8 Mod								
Material	Aluminum Alloy								
Weight (Product)	≈1203g	≈1278g	≈1300g	≈1262g	≈1963g	≈1466g	≈1654g	≈1994g	≈1950g